

ECON-O-WASH ECON-O-DRY

SMALL LOAD EFFICIENCY FOR ON-PREMISE LAUNDRIES

Used as a team, the Econ-O-Wash topload washer and the Econ-O-Dry
singleload or stacked dryer effectively clean and dry smaller loads
quickly and efficiently—improving on-premise laundry productivity.



ECON-O-WASH

TOPLOAD WASHERS



Four Vane Agitator



Automatic Balance System



Heavy-

Durability

The Econ-O-Wash topload is constructed for unmatched longevity. It features a durable porcelain enamel washtub, a scratch-resistant, hard-baked porcelain enamel top and lid, a heavy-duty, two-speed motor, and a corrosion-resistant polypropylene pump—all wrapped up in a rugged galvanized steel cabinet!

Energy Efficiency & High Spin Speed

Unlike most home-style topload washers, which guzzle around 151 liters of water per load, The Econ-O-Wash topload is engineered with a water saving feature that uses just 89.6 liters per load! By using less water, on-premise laundries significantly cut hot water consumption—saving energy and lowering utility costs! Moreover, the washer delivers 710 RPM spin speeds to remove more water from every load. In doing so, dry time is reduced—increasing productivity and reducing utility costs! The Econ-O-Wash topload offers superior energy efficiency. At start-up the machine draws fewer amps—conserving additional electricity. No wonder this washer conforms to the Department of Energy (DOE) 2007 efficiency standards.

Quality of the Wash

Superior engineering means laundry gets cleaner. The Econ-O-Wash topload features a curved, four-vane polypropylene agitator with a 210 degree agitator stroke—the longest in the industry. The machine's lengthy stroke delivers increased wash action thereby generating superb wash results.

Automatic Balance System

Designed to automatically adjust out-of-balance loads, Econ-O-Wash completes wash cycles quietly, smoothly and without interruption. The liquid-filled balance ring at the top of the tub and the washer's advanced suspension design combine to eliminate interrupted wash cycles due to out-of-balance loads. The feature also eliminates the need for an out-of-balance switch!

User-friendly Control

Econ-O-Wash makes it easy for laundry room attendants to select from several wash cycles. The user simply chooses a cycle—normal, permanent press, delicate, or one of three unique energy-saving cycles—and presses start. It offers three water temperature options for the wash cycle—hot, warm and cold—along with an indicator light that illuminates when the machine is in use.



Econ-O-Wash Topload Washer

- 710 RPM spin speed
- Three water- and energy-saving cycle options
- Scratch-resistant, hard-baked porcelain enamel top and lid
- Automatic balance system
- Durable porcelain enamel washtub
- 100% front serviceability
- Rear self-leveling legs
- Galvanized steel cabinet
- Heavy-duty, two-speed motor



**AFFORDABLE
EFFICIENCY**

Heavy-Duty Drain Hose



Econ-O-Dry Singleload Dryer

- Oversized door opening
- Extra large cylinder capacity
- Front serviceability
- Easy access front lint filter
- Easy-to-use control
- Gas or electric heat
- Reversible door

Econ-O-Dry Doubleload Dryer

- Doubleload capacity
- Front serviceability
- Easy access front lint filter
- Easy-to-use control
- Gas or electric heat
- Reversible doors

A perfect match to Econ-O-Wash topload washers, **Econ-O-Dry dryers**—in singleload or stacked doubleload capacity—are not only easy to use, they dry laundry incredibly fast!

Robust Door and Cylinder

Equipped with an oversized door opening, Econ-O-Dry dryers make loading and unloading a snap using a sensible ergonomic design. The robust cylinder capacity takes on larger loads of laundry and provides improved tumble action through axial airflow technology—moving air more evenly through laundry items to get them dry faster!

Easy to Service & Maintain

Designed for minimal maintenance and simplified serviceability, the drying tumbler features a lint filter that's easy to reach and clean, but doesn't get in the way. Moreover, when service is necessary, most components are accessible from the front of the machine. The motor, blower, heating element, gas valve and thermostats are serviceable through a lower front panel without disconnecting the door switch.

Save Space—Double Production

By selecting the stack Econ-O-Dry model, on-premise laundries double drying capacity using half the space. The stack model offers two individually operable, single-pocket tumblers in one of the narrowest cabinets available (26.875 inches wide). This allows laundries to maximize space and productivity.

Flexible Control

The dryer control offers fabric selection options including delicate, permanent press, no heat and normal, and an indicator light that illuminates when the machine is in use. A convenient timer enables the user to manually select dry time according to load type and size.

Gas or Electric

Econ-O-Dry dryers are available in gas or electric heat —making them the right choice for any on-premise laundry. United Laboratories (UL) listed, Econ-O-Dry is built to last for years of trouble-free operation.

Oversized Door Opening



Easy-to-Use Control



**UNMATCHED
DURABILITY**

**ECON-O-DRY
SINGLELOAD AND
STACKED DOUBLELOAD**

ECON-O-WASH

ON-PREMISE LAUNDRY

EW65

DIMENSIONS & WEIGHTS

Cylinder Volume cu. ft (dm ³)	2.8 (79)
Net Weight lbs (kg)	190 (86)
Crated Weight lbs (kg)	210 (95)
Machine Width inch (mm)	25.625 (651)
Machine Depth inch (mm)	28 (711)
Machine Height inch (mm)	43 (1092)
Floor to Work Surface inch (mm)	36 (914)
Shipping Dimension inch (mm)	28 x 30 x 45 (WxDxH) (711 x 762 x 1143)
Available Colors	white

GENERAL

Washing Speed	
High Speed strokes per min	67
Low Speed strokes per min	44
Spin Speed 2-Speed	
High Speed rpm	710
Low Speed rpm	473

CONNECTIONS

Drain Diameter inch (mm)	1-1/2 (38.1)
Water Inlet inch (mm)	3/4 (19)
Water Pressure psi (bar)	20-120 (1.4/8.3)
Water Flow gal/min (l/min)	37.5 (140)
Motor Power Hp	1/2
Amp Protection Amp	
120/60/1	15
230/50/1	10



ECON-O-DRY

ON-PREMISE LAUNDRY

ED9E
ED9G

EDS9E
EDS9G

DIMENSIONS & WEIGHTS

Basket Volume cu. ft (dm ³)	7.0 (199)	7.0 (199)
Net Weight		
Electric lbs (kg)	135 (61)	265 (120)
Gas lbs (kg)	140 (64)	275 (125)
Crated Weight		
Electric lbs (kg)	145 (66)	280 (127)
Gas lbs (kg)	150 (68)	290 (132)
Machine Width inch (mm)	26.875 (683)	26.875 (683)
Machine Depth inch (mm)	28 (711)	28 (711)
Machine Height inch (mm)	43 (1092)	76.625 (1946)
Door Opening inch (mm)	24.7 (628)	24.7 (628) per basket
Shipping Dimension inch (mm)	29.5 x 30.5 x 45 (WxDxH) (749 x 775 x 1143)	30 x 33 x 80 (762 x 838 x 2032)
Available Colors	white	white

CONNECTIONS

Exhaust Diameter inch (mm)	4 (102)	4 (102)
Exhaust Air Flow cfm (m ³ /min)	220 (6.23)	220 (6.23) per basket
Basket Motor Power Hp	1/3	1/3 per basket
Gas Heating BTU/h (Kcal/h)	25,000 (6300)	25,000 (6300) per basket
Gas Inlet Diameter inch	3/8 N.P.T.	3/8 N.P.T.
Heating Element Wattage		
60Hz – 208 Volt**	4750	4750
240 Volt	5350	5350
50Hz – 230 Volt	4800	4800
Australia 230 Volt	4000	4000
Amp Protection Amp		
Gas	120/60/1 15 230/50/1 10	15 per basket 10 per basket
Electric	120/240/60/1 30 230/50/1 30 Australia 230/50/1 20	30 per basket 30 per basket 20 per basket

* Product design and specifications are subject to change without notice. For the most current and complete technical specifications, contact Laundry Solutions Australia for details.

** Conversion kit required for 208 volt models. Contact Laundry Solutions Australia for details

DISTRIBUTED BY:



www.yourlaundry.com.au

• 1 800 243 477

1/6 Redland Drive MITCHAM, VIC 3132

• FAX 1300 728 108